

CLAIMS

1. A device for postcoital positioning of a female user comprising:

 a first planar surface adapted to extend vertically while said device is

 in use, said first planar surface having an upper and a lower edge;

 a second planar surface adapted to extend horizontally when said

device is in use and extending perpendicularly relative to said first planar surface,
said second planar surface having a front and a rear edge;

 with said lower edge of said first planar surface extending

contiguously with said rear edge of said second planar surface; and

 a continuous curved surface extending from said upper edge of said

first planar surface to said front edge of said second planar surface;

 said curved surface having a convex configuration adjacent said upper
edge and a concave configuration adjacent said front edge.
2. A device for enabling a female user to comfortably retain after sexual
intercourse a position that will enhance the likelihood of becoming pregnant
comprising:

 a lower section adapted to be placed beneath the buttocks of a user to
maintain the hips of said user in an elevated position; and

an upper section extending vertically upwardly from said lower section for at least 16 inches to support the legs of said user in a generally upright position.

3. A postcoital positioning device for maintaining a female user after sexual intercourse in a position for achieving conception comprising:

a concave lower portion adapted to be placed beneath the buttocks of a user to maintain the hips of said user in a raised position; and

a convex portion extending from said lower portion to maintain the legs of said user in a generally vertical upright position while said buttocks are supported upon said lower concave portion.

4. A device for postcoital positioning of female user comprising:

a concave lower portion adapted to be placed beneath the buttocks of a user to support said buttocks and having a width sufficient to maintain the hips of said user in an elevated position; and

a convex upper portion contiguous with said lower portion and extending upwardly there from when said device is in use a distance sufficient to maintain the legs of said user in an upwardly directed position while said buttocks are supported upon said lower portion.

5. A device for postcoital positioning of a female user comprising:
means for elevating the buttocks of said user; and
means cooperating with said elevating means for simultaneously supporting the legs of said user in a generally upright position.
6. A device according to Claims 1-5 comprising a base member made of foam rubber.
7. A device according to Claim 6 comprising a removable cover extending about said foam rubber base member and enclosing said base member therein.
8. A device according to Claims 1-7 comprising a width of between 14 and 18 inches and a height of between 16 and 20 inches.
9. A device according to Claim 1 wherein said first planar surface and said second planar surface have a width of between 14 and 18 inches; wherein said first planar surface has a height of between 16 and 20 inches; wherein said second planar surface has a depth of between 18 and 25 inches; said device further comprising a thickness extending between said first planar surface and said curved surface of between 8 and 12 inches.
10. A device according to Claims 1-9 comprising a pair of handles located on opposite sides thereof to facilitate use of said device.

11. A device according to Claim 1 wherein said concave configuration tapers toward said front edge to meet said second planar surface to form an attenuated configuration therewith.